

SOLVENT 142  
547181

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	SOLVENT 142
Product code	547181
Product Use Description	No data

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: liquid,, clear

CAUTION! COMBUSTIBLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF INHALED. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

**Potential Health Effects**

**Routes of exposure**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

**Eye contact**

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

**Skin contact**

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get

SOLVENT 142  
547181

into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

**Inhalation**

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

**Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:., Skin, lung (for example, asthma-like conditions)

**Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:., stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness)

**Target Organs**

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

**Carcinogenicity**

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

**Reproductive hazard**

No data

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Components</b>	<b>CAS-No.</b>	<b>Concentration</b>
SOLVENT NAPHTHA	64742-88-7	<=100%

SOLVENT 142  
547181

<b>Components</b>	<b>CAS-No.</b>	<b>Concentration</b>
(PETROLEUM), MEDIUM ALIPHATIC		

#### **4. FIRST AID MEASURES**

##### **Eyes**

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

##### **Skin**

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

##### **Ingestion**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

##### **Inhalation**

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

##### **Notes to physician**

**Hazards:** This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

**Treatment:** No information available.

#### **5. FIRE-FIGHTING MEASURES**

##### **Suitable extinguishing media**

Dry chemical, Foam, Carbon dioxide (CO<sub>2</sub>)

##### **Hazardous combustion products**

carbon dioxide and carbon monoxide, hydrocarbons

SOLVENT 142  
547181

**Precautions for fire-fighting**

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

**Flammability Class for Flammable Liquids**

Combustible Liquid Class IIIA

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions**

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

**Environmental precautions**

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

**Methods for cleaning up**

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

**7. HANDLING AND STORAGE**

**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

SOLVENT 142  
547181

**Storage**

Store in a cool, dry, ventilated area away from sources of heat, moisture, and incompatible substances.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Guidelines**

**General advice**

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Exposure controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

**Eye protection**

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

**Skin and body protection**

Wear resistant gloves (consult your safety equipment supplier).  
To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory protection**

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

SOLVENT 142  
547181

<b>Physical state</b>	liquid
<b>Form</b>	No data
<b>Colour</b>	clear
<b>Odour</b>	hydrocarbon-like
<b>Boiling point/boilingrange</b>	355.00 °F / 355 °F
<b>pH</b>	No data
<b>Flash point</b>	152.8 °F / 67.1 °C
<b>Evaporation rate</b>	151 (Ethyl Ether)
<b>Explosion limits</b>	1.0 %(V) 7.0 %(V)
<b>Vapour pressure</b>	0.13 mmHg @ 68 °F / 20 °C
<b>Vapour density</b>	5.48
<b>Density</b>	0.79 g/cm3 @ 60.00 °F / 15.56 °C 6.59 lb/gal @ 61 °F / 16 °C
<b>Solubility</b>	negligible in water
<b>Partition coefficient: n-octanol/water</b>	No data
<b>log Pow</b>	no data available
<b>Autoignition temperature</b>	600 °F / 316 °C

## 10. STABILITY AND REACTIVITY

### Stability

Stable.

### Conditions to avoid

### Incompatible products

strong oxidizing agents

### Hazardous decomposition products

carbon dioxide and carbon monoxide, hydrocarbons

### Hazardous reactions

Product will not undergo hazardous polymerization.

### Thermal decomposition

No data

SOLVENT 142  
547181

**11. TOXICOLOGICAL INFORMATION**

**Acute oral toxicity**

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC	LD 50 Rat: > 5,000 mg/kg
--	--------------------------

**Acute inhalation toxicity**

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC	LC 50 Rat: > 5500 ppm, 4 h
--	----------------------------

**Acute dermal toxicity**

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC	LD 50 Rabbit: > 3,000 mg/kg
--	-----------------------------

**12. ECOLOGICAL INFORMATION**

**Aquatic toxicity**

**Acute and Prolonged Toxicity to Fish**

No data

**Acute Toxicity to Aquatic Invertebrates**

No data

**Environmental fate and pathways**

No data

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal methods**

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

**14. TRANSPORT INFORMATION**

